



## **NOTES**

- 1. Raised pavement markers shall be installed only when specified in the Contract Plans.
- 2. See the Standard Plans for marker designation.
- 3. The portion labeled "OPTIONAL" is only used when the Optional Marked Deceleration Taper (see Standard Plans M-3.10 and M-3.20) is specified in the contract plans.

## **LEFT TURN LANE**



## TWO-WAY LEFT TURN LANE





## LONG LINE SUPPLEMENT WITH RAISED PAVEMENT **MARKERS ~ TURN LANES STANDARD PLAN M-20.40-00**

SHEET 1 OF 2 SHEETS

APPROVED FOR PUBLICATION

Harold J. Peterfeso

03-04-05


**END TWO-WAY LEFT TURN LANE** 

NOTE: THIS PLAN IS NOT A LEGAL ENGINEERING DOCUMENT BUT AN ELECTRONIC DUPLICATE. THE ORIGINAL, SIGNED BY THE ENGINEER AND APPROVED FOR PUBLICATION, IS KEPT ON FILE AT THE WASHINGTON STATE DEPARTMENT OF TRANSPORTATION. A C

TYPE 2YY RPMs ≈ 10' O.C. (TYP.)

DOUBLE YELLOW CENTER LINE

**DETAIL "D"** 



4" (TYP.)

**DETAIL "E"** 

INSIDE EDGE OF LANE

03-04-05

Harold J. Peterfeso

15' - 0"